

# Three Seam Pillow Case

## Fabric Requirements

All fabric will be cut from selvage to selvage

BODY of Pillow Case

3/4 YD - cut to 27" x WOF

CUFF

1/4 YD - cut to 9" x WOF

ACCENT (optional)

1/8 YD - cut to 3" x WOF

Press in half wrong sides together, along length

- 1) Lay 9" CUFF piece RIGHT side up on work surface.
- 2) Lay the ACCENT Piece, pressed with right sides out on top of CUFF, lining up raw edges at the top.
- 3) Lay BODY of Pillow Case RIGHT side DOWN on top of CUFF and ACCENT piece lining up all raw edges.
- 4) ROLL the Body of pillowcase from bottom to top then FOLD the CUFF piece up around the BODY and ACCENT piece and match the raw edges.
- 5) PIN all raw edges together, you should have five edges (three if there is no accent strip), one CUFF edge, with two edges of the ACCENT STRIP and one edge of the BODY piece and one edge of the CUFF.
- 6) Making a FRENCH SEAM
- 7) Stitch along the edges using a 1/4" seam. Then, TURN inside out. You now have a finished edge with all the stitching inside.
- 8) FOLD the pillowcase so that the WRONG sides are together. STITCH a scant quarter inch seam down one side and across the bottom.
- 9) Line up the Pillowcase so that the right sides are together and STITCH a 3/8" seam encasing the raw edges of the first seam.
- 10) TURN back to right sides out.

Hooray!! You have a finished pillowcase.

Online Directions: <http://millionpillowcases.allpeoplequilt.com/>